

ENGLISH TRANSLATION OF THE INTERNATIONAL APPLICATION
FOR NATIONAL PHASE SUBMISSION

12

Patent Claims

1. A method for detaching a frozen charge (5) from the inner wall of a grinding pipe (1), characterized in that the drive device (2) of the grinding pipe (1) is controlled for targeted detachment of the frozen charge (5).

2. The method as claimed in claim 1, characterized in that the angle of rotation (φ) and speed of rotation of the grinding pipe (1) are varied by the drive device (2).

3. The method as claimed in claim 2, characterized in that a maximum value of the angle of rotation (φ) smaller than 180° is not exceeded.

4. The method as claimed in claim 2, characterized in that a maximum value of the angle of rotation (φ) smaller than or equal to 90° is not exceeded.

5. The method as claimed in one of claims 2 to 4, characterized in that the maximum value of the angle of rotation (φ) is dependent on the material nature of the frozen charge (5).

6. The method as claimed in one of claims 2 to 5, characterized in that the angle of rotation (φ) is set to oscillate about at least one predetermined angle of rotation (φ_1 , φ_2).

7. The method as claimed in one of claims 2 to 6, characterized in that the angle of rotation (φ) is set to

ENGLISH TRANSLATION OF THE INTERNATIONAL APPLICATION
FOR NATIONAL PHASE SUBMISSION

13

oscillate about a number of predetermined angles of rotation (φ_1 or φ_2) with the same sign one after another.

8. The method as claimed in one of claims 2 to 7, characterized in that the angle of rotation (φ) is set to oscillate about a number of predetermined angles of rotation (φ_1 , φ_2) with different signs one after another.

9. The method as claimed in one of the preceding claims, characterized in that the grinding pipe (1) is braked abruptly at least once at a predetermined angle of rotation (φ).

10. The method as claimed in claim 9, characterized in that the grinding pipe (1) is braked abruptly to a standstill.

11. The method as claimed in one of the preceding claims, characterized in that the same motor is used for detaching the frozen charge (5) as for rotating the grinding pipe (1) during grinding operation.

12. The method as claimed in one of the preceding claims, characterized in that the frozen charge (5) is wetted.

13. A control device (3) for the drive device (2) of a grinding pipe (1) for carrying out a method as claimed in one of the preceding claims.

14. The control device (3) as claimed in claim 13, characterized in that it has means for defining an operating cycle for the grinding pipe (1).

ENGLISH TRANSLATION OF THE INTERNATIONAL APPLICATION
FOR NATIONAL PHASE SUBMISSION

14

15. The control device (3) as claimed in claim 13 or 14, characterized in that it has a field-oriented regulating arrangement.

16. A drive device (2) for a grinding pipe (1) with a control device (3) as claimed in one of claims 13 to 15.

17. The drive device (2) as claimed in claim 16, characterized in that it has a motor which drives the grinding pipe (1) both during grinding operation and for detaching the frozen charge (5).

18. The drive device (2) as claimed in claim 17, characterized in that the motor is coupled to a converter.

19. The drive device (2) as claimed in claim 17 or 18, characterized in that the motor is a ring motor.